

## HOW TO INSTALL WINDOW VISORS WITH CLIPS

**FIRST:** Thoroughly wash vehicle. If paint sealant is on it, use a wax and grease remover to clean area where tape will adhere. The tape supplied on item adheres and cures best at temperatures above 65° (F). If below 65°, warm contact area of vehicle and tape supplied on the deflector using a hot air gun or hair dryer. Thoroughly clean the visor contact area with the alcohol pads



provided. If pads still show dirt residue, further clean area with clean rags and rubbing alcohol. **IMPORTANT:** The area where tape adheres must be clean and dry. Do not touch after cleaning! Clean one side of vehicle at a time. Use a paper towel to wipe a small area and discard. Do not fold it, or wipe a large area with it as this will only smudge contaminants on the vehicle.



**Step 1:**  
Prepare to remove rubber liner with tool.



**Step 6:**  
Line up visors onto car



**Step 2:**  
Once started with tool pull enough off to install clips but not all off the weather strip.



**Step 7:**  
Line up hole in visor with clip (may need to slide clip a little to line up)



**Step 3:**  
Install clips



**Step 8:**  
Install included washer on back of clip and insert peg into front of visor to clip together.



**Step 4:**  
Line up clips to holes in visors.



**Step 9:**  
Once all clips are installed, start to pull the tape liner from the visors careful not to rip. Slowly and firmly apply pressure to the visor to adhere to the car.



**Step 5:**  
Fold over tape backing just enough to be able to pull once adhered to vehicle.



**Step 10:**  
Make sure all visor tape is adhered to the vehicle. Do not wash vehicle for 48 hours. (Rain is OK)